



CERTIFICATE OF ACCREDITATION

The ANSI National Accreditation Board

Hereby attests that

J&L Dimensional Services, Inc.

16 Industrial Parkway

La Porte, IN 46350

Fulfills the requirements of

ISO/IEC 17025:2017

In the field of

DIMENSIONAL MEASUREMENT

This certificate is valid only when accompanied by a current scope of accreditation document.
The current scope of accreditation can be verified at www.anab.org.

A handwritten signature in black ink, appearing to be 'J. Stine', is located on the left side of the certificate.

Jason Stine, Vice President

Expiry Date: 27 May 2027

Certificate Number: L2256



This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory
quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

J&L Dimensional Services, Inc.

16 Industrial Parkway
La Porte, IN 46350

Marta Juszczak 219-325-3588

DIMENSIONAL MEASUREMENT

ISO/IEC 17025 Accreditation Granted: 27 May 2025

Certificate Number: L2256

Certificate Expiry Date: 27 May 2027

1 Dimensional

Parameter/Equipment	Range	Expanded Uncertainty of Measurement (+/-)	Reference Standard, Method, and/or Equipment
Dimensional Measurement 1D	(0 to 12) in	0.001 0 in	Measurement using Caliper
	(0.5 to 8) in	0.001 0 in	Measurement using Inside Micrometer
	(0 to 1) in	0.001 0 in	Measurement using Outside Micrometer
	(0 to 1) in	0.001 0 in	Measurement using Depth Micrometer
	(0 to 1) in	0.001 0 in	Measurement using Drop Indicator
	(0 to 0.04) in	0.000 63 in	Measurement using Test Indicator
	(0 to 0.8) in	0.001 0 in	Measurement using OD Snap Gauge
	(0 to 24) in	0.001 1 in	Measurement using Height Gauge

2 Dimensional

Parameter/Equipment	Range	Expanded Uncertainty of Measurement (+/-)	Reference Standard, Method, and/or Equipment
Dimensional Measurement 2D	(0 to 8) in	590 μ in	Measurement using Optical Comparator

3 Dimensional

Parameter/Equipment	Range	Expanded Uncertainty of Measurement (+/-)	Reference Standard, Method, and/or Equipment
Dimensional Measurement 3D	(0 to 40) in	0.001 4 in	Measurement using Coordinate Measuring Machine
	(0 to 48) in	0.001 9 in	Measurement using Structured Light

Calibration and Measurement Capability (CMC) is expressed in terms of the measurement parameter, measurement range, expanded uncertainty of measurement, and reference standard, method, and/or equipment. The expanded uncertainty of measurement is expressed as the standard uncertainty of the measurement multiplied by a coverage factor of 2 ($k=2$), corresponding to a confidence level of approximately 95%.



Jason Stine, Vice President